




Aluminum & Aluminum-Alloy
Extruded Round Tubes for General Purpose Applications
(ASTM B 491)

ALUMINUM COILED TUBING (standard sizes that are available)



DAYCO offers extruded round tubular product for general purpose applications in coil form for use such as refrigeration service, gas lines, instrument lines and oil lines. Made for the O.E.M. who straightens then bend, flare or shape the tube for their end use products.



“Tube in Coil”

Standard Drawn Level Wound Coil (LWC)				
Normal Size (in.)	O.D. (in.)	Ovality (in.)	Wall (in.)	Wt/Ft (lbs.)
.375 x .049	.376 ± .003	± .006	± .003	0.0592
.500 x .049	.502 ± .003	± .011	± .003	0.0820
.625 x .049	.627 ± .003	± .017	± .003	0.1046
.750 x .049	.753 ± .003	± .025	± .003	0.1275
Non-Standard Drawn Level Wound Coil (LWC)				
O.D. Size (in.)	Wall (in.)	O.D. Size (mm)	Wall (mm)	
0.150 to 2.000	≥ 0.015	4 to 50	≥ 0.4	

Coils available in “Bulk” package and wound on cardboard “Reels”.



Dayco Industries, LLC • 10215 San Sevaine Way • Mira Loma, CA 91752
 Call Toll Free: (800) 893-8355 • Local: (951) 360-5900 • Fax: (951) 360-6198
 E-mail: Sales@daycoindustries.com